



A WATTS Brand

S19-921 On-Site® Gravity-Fed Eyewash

- Exceeds American National Standard Z358.1 Specifications
- Includes wall-mounting bracket, universal identification sign and inspection tag
- Full, one-year warranty — water preservative not included

Specifications

Self-contained eyewash unit is ideal anywhere water supply is not available. Flushes eyes for 15 minutes at a minimum of 0.4 gallons/minute by using only 7 gallons of water. Translucent tank assembly lets you see at a glance when it is time to clean or refill the tank. Sturdy pedestal with hinged eyewash tray pulls down in one quick motion. Removable tank is inverted onto pedestal, piercing a liner. Stainless steel clamps hold tank to pedestal. When arm is pulled down, water flow is activated.

☒ **This unit is not rated for outdoor use.**

Construction

Refillable eyewash tank fills to 7 gallons. Weighs 60 lb filled and 3.5 lb empty. Translucent tank made of impact resistant plastic. Pedestal supports the eyewash tank and weighs 6 lb. The yellow pedestal and black pull-down arm are made of impact-resistant and chemical-resistant plastic. Wall bracket is stainless steel.

Standard Equipment

Tank

14"H x 22"W x 9"D tank made of translucent white high-density polyethylene.

Pedestal

13½"H x 22"W x 18½"D pedestal made of opaque yellow polypropylene, with a black polypropylene pull-down arm.

Wall Bracket

Stainless steel mounting bracket.



Waste

Nipple for ½" I.D. tube.



Model	Description
○ S19-921	On-Site Gravity Fed Eyewash

Dimensions



(mm)