



A WATTS Brand

# COL-2B, COL-3B, COL-4B, COL-5B, COL-6B Column Beach Showers, 2-6 Person

## Specifications

### Materials

All exposed parts are type 304 stainless steel or polished chrome-plated brass. Valve manifold is cast brass. Drain fitting is cast iron and supply inlets are copper tubing.

## Standard Equipment

### Flow Control

A 1.5 GPM (5.7 LPM) flow control is standard. Actual flow may vary, but will not exceed 2.0 GPM (7.6 LPM) max.

### Column Shower

Constructed of type 304 stainless steel. Column and column cap are 16 gauge, and base flange is 13 gauge. Access panel located near bottom of column.

### Drain Type

Drain type A: supplies from below, vent off drain line.

### Supply Inlets

Constructed of 3/4" type "L" copper tubing.



The standard beach shower is arranged less drain slots.



## Standard Selections (Must select one from each category)

### Model No. (select one)

Description	Showerheads	Foot Sprays
<b>COL-2B</b> 2-Person Column Shower	1	1
<b>COL-3B</b> 3-Person Column Shower	2	1
<b>COL-4B</b> 4-Person Column Shower	3	1
<b>COL-5B</b> 5-Person Column Shower	4	1
<b>COL-6B</b> 6-Person Column Shower	5	1

### Drain Type (select one)

**A** Off-line vent with supplies from below

### Showerhead Height (select one)

**6'-0"** Standard Height  
**5'-6"** Juvenile Height

### Valve Type (select one)

Single Tempered/Cold Supply

**AST** Air Pushbutton  
**SV** Single Compression Valve

### Showerhead Type (select one)

**S15** Standard Showerhead (Flow Rate = 1.5 GPM/5.7 LPM)  
**S20** Standard Showerhead (Flow Rate = 2.0 GPM/7.6 LPM)

### Supply Stop Type (select one)

**ST** Stops in each Supply  
**NONE** No Supply Stops

### Drain Variant Type (select one)

**D** Standard Drain  
**DG** Dome Grate Drain  
**LD** Less Column Drain

### Ship Drain in Advance (select one)

**Y** Yes \*  
**N** No, Ship Drain with Unit  
**NONE** Less Column Drain Selected †

### Column Drain Slot Type (select one)

**WS** With Column Drain Slots  
**LS** Less Column Drain Slots

### Clamping Ring Type (select one)\*

**CR** Clamping Ring for Flashing  
**NONE** No Clamping Ring for Flashing

\* Only available with D or DG Drain Variant Type

† Only available with LD Drain Variant Type

2.0 GPM and 2.5 GPM showerhead flow rates do not meet California Energy Commission 20 CCR T.20, Div. 2, 1601-1609